

TOP ALUMINIUM 250

This is a glossy architectural decorative aluminium paint for wooden and metallic surfaces. Its brilliant reflective property serves as a protective finish for storage tanks, ducting and pipes. It can also be used as a primer for wood surface.

Standard	Equivalent to Malaysian Standard 289:1985	
Colour	Aluminium	
Pack Size	1, 5 and 18 litres	
Composition	<i>Binder</i>	Modified hydrocarbon derivative
	<i>Pigment</i>	Aluminium flakes
	<i>Solvent</i>	Hydrocarbon mixture
Volume Solid	33 ± 2%	
Recommended Dry Film thickness	20 – 30 microns (per coat)	
Drying Times *	<i>Touch Dry</i>	Within 1 hour
	<i>Hard Dry</i>	Within 4 hours
Over-coating Interval *	Minimum 8 hours	
Spreading Rate *	11 – 16 m ² / litre/ coat	
Application	<i>Brush</i>	Use as is
	<i>Conventional Spray</i>	Use as is, thin not exceeding 5% by volume with paint thinner or white spirit/ mineral turpentine if necessary
Surface Preparation	<u><i>New Unpainted Surface</i></u>	<u><i>Previous Painted Surface</i></u>
<i>Metal/Mild Steel</i>	<ul style="list-style-type: none"> Remove rust or mill scales by manual or mechanical cleaning Ensure surface free from oil, grease and other contaminant 	<ul style="list-style-type: none"> Remove loose adhering paint Remove debris, oil, grease or other contaminant before painting Use suitable primer
<i>Wood/Timber</i>	<ul style="list-style-type: none"> Ensure surface free from oil, grease and other contaminant Sand surface with abrasive paper for better adhesion and appearance 	<ul style="list-style-type: none"> Remove loose adhering paint Ensure surface is clean and dry Use suitable primer
Recommended Painting System	<u><i>Sequence</i></u>	<u><i>Product</i></u>
<i>Metal/Mild Steel</i>	Primer (1 coat)	TOP GREYGREEN OXIDE 437
	Finish (2 coats)	TOP ALUMINIUM 250
<i>Wood/Timber</i>	Finish (2 coats)	TOP ALUMINIUM 250

* Based on recommended thickness; will vary considerably with surface characteristics, application techniques, weather and wastage.

The corresponding Safety Data Sheet (SDS) for this product shall be provided upon request.

Further inquiry and SDS request can be made to transpaint@yungkong.com

Manufactured by: **Trans Paint Coatings Sdn Bhd**. Lot 1393, Jalan Meranti, Bintawa Industrial Estate, 93450 Kuching, Sarawak, Malaysia.

Tel: +6082 334 222 Fax: +6082 339 189 Website: www.transpaint.yungkong.com

While every care has been taken to ensure the accuracy of the information contained in this data sheet, it is provided in good faith and that no liability can be accepted arising from its use. Where the conditions of use warrant it, it is recommended that the data are checked to ensure their suitability for the use envisaged.

Revision: **20 JUL 2023**

<end of document>