

## TOP CAT KILAT

This is an economical gloss paint for interior as well as limited exterior surfaces. It is easy to apply and has a high gloss finish. It can be used on metal/ wooden railings, frames, doors, panels, etc.

<b>Colour</b>	<i>See Cat Kilat Colour Card</i>	
<b>Pack Size</b>	0.25 (selected colours only), 1, and 5 litres	
<b>Composition</b>	<i>Binder</i>	Long-oil alkyd
	<i>Pigment</i>	Inorganic and organic pigments
	<i>Solvent</i>	Hydrocarbon mixture
<b>Volume Solid</b>	44 ± 2% for standard white, varying with colours	
<b>Recommended Dry Film thickness</b>	25 – 35 microns (per coat)	
<b>Drying Times *</b>	<i>Touch Dry</i>	Within 4 hours
	<i>Hard Dry</i>	Within 8 hours
<b>Full Cure *</b>	3 – 4 weeks; Time for the coating to reach its full chemical/mechanical properties and will resist and perform as per the properties featured	
<b>Over-coating Interval *</b>	Minimum 8 hours	
<b>Spreading Rate *</b>	12 – 17 m <sup>2</sup> /litre/coat	
<b>Application</b>	<i>Brush/Roller</i>	Use as is, thin not exceeding 5% by volume with paint thinner or white spirit/mineral turpentine if necessary
	<i>Conventional Spray</i>	Thin with paint thinner or white spirit/mineral turpentine to 20% by volume
	<i>Airless Spray</i>	Use as is
<b>Surface Preparation</b>	<u><i>New Unpainted Surface</i></u>	<u><i>Previous Painted Surface</i></u>
<i>Metal/Mild Steel</i>	<ul style="list-style-type: none"> <li>Remove rust or mill scales by manual or mechanical cleaning</li> <li>Ensure surface free from oil, grease and other contaminant</li> </ul>	<ul style="list-style-type: none"> <li>Remove loose adhering paint</li> <li>Remove debris, oil, grease or other contaminant before painting</li> <li>Use suitable primer</li> </ul>
<i>Wood/Timber</i>	<ul style="list-style-type: none"> <li>Ensure surface free from oil, grease and other contaminant</li> <li>Sand surface with abrasive paper for better adhesion and appearance</li> </ul>	<ul style="list-style-type: none"> <li>Remove loose adhering paint</li> <li>Ensure surface is clean and dry</li> <li>Use suitable primer</li> </ul>
<b>Recommended Painting System</b>	<u><i>Sequence</i></u>	<u><i>Product</i></u>
<i>Metal/Mild Steel</i>	Primer (1 coat) Undercoat (1 coat) Finish (2 coats)	TOP GREYGREEN OXIDE 437 TOP CAT KILAT UNDERCOAT <b>TOP CAT KILAT</b>
<i>Wood/Timber</i>	Undercoat (1 coat) Finish (2 coats)	TOP CAT KILAT UNDERCOAT <b>TOP CAT KILAT</b>

\* Based on recommended thickness; will vary considerably with surface characteristics, application techniques, weather and wastage.

The corresponding Safety Data Sheet (SDS) for this product shall be provided upon request.

Further inquiry and SDS request can be made to [transpaint@yungkong.com](mailto:transpaint@yungkong.com)

Manufactured by: **Trans Paint Coatings Sdn Bhd**. Lot 1393, Jalan Meranti, Bintawa Industrial Estate, 93450 Kuching, Sarawak, Malaysia.

Tel: +6082 334 222 Fax: +6082 339 189 Website: [www.transpaint.yungkong.com](http://www.transpaint.yungkong.com)

While every care has been taken to ensure the accuracy of the information contained in this data sheet, it is provided in good faith and that no liability can be accepted arising from its use. Where the conditions of use warrant it, it is recommended that the data are checked to ensure their suitability for the use envisaged.

Revision: **20 JUL 2023**

<end of document>