

CAT KAYU

This is a multi-purpose economical gloss paint for decoration and marking paint for wood, metal and other surfaces.

Colour	See Cat Kayu Colour Card	
Pack Size	1 litre	
Composition	<i>Binder</i>	Petroleum derivative
	<i>Pigment</i>	Inorganic and organic pigments
	<i>Solvent</i>	Hydrocarbon mixture
Volume Solid	45 ± 2% for standard white, varying with colours	
Recommended Dry Film thickness	30 – 40 microns (per coat)	
Drying Times *	<i>Touch Dry</i>	Within 2 hours
	<i>Hard Dry</i>	Within 4 hours
Over-coating Interval *	Minimum 4 hours	
Spreading Rate *	11 – 14 m ² /litre/coat	
Application	<i>Brush/Roller</i>	Use as is
Surface Preparation	<u><i>New Unpainted Surface</i></u>	<u><i>Previous Painted Surface</i></u>
<i>Metal/Mild Steel</i>	<ul style="list-style-type: none"> Remove rust or mill scales by manual or mechanical cleaning Ensure surface free from oil, grease and other contaminant 	<ul style="list-style-type: none"> Remove loose adhering paint Remove debris, oil, grease or other contaminant before painting
<i>Wood/Timber</i>	<ul style="list-style-type: none"> Ensure surface free from oil, grease and other contaminant Sand surface with abrasive paper for better adhesion and appearance 	<ul style="list-style-type: none"> Remove loose adhering paint Ensure surface is clean and dry
Recommended Painting System	<u><i>Sequence</i></u>	<u><i>Product</i></u>
<i>Metal/Mild Steel</i>	Finish (2 coats)	CAT KAYU
<i>Wood/Timber</i>		

* Based on recommended thickness; will vary considerably with surface characteristics, application techniques, weather and wastage.

The corresponding Safety Data Sheet (SDS) for this product shall be provided upon request.

Further inquiry and SDS request can be made to transpaint@yungkong.com

Manufactured by: **Trans Paint Coatings Sdn Bhd**. Lot 1393, Jalan Meranti, Bintawa Industrial Estate, 93450 Kuching, Sarawak, Malaysia.

Tel: +6082 334 222 Fax: +6082 339 189 Website: www.transpaint.yungkong.com

While every care has been taken to ensure the accuracy of the information contained in this data sheet, it is provided in good faith and that no liability can be accepted arising from its use. Where the conditions of use warrant it, it is recommended that the data are checked to ensure their suitability for the use envisaged.

Revision: **20 JUL 2023**

<end of document>