

NU-COTE WATERLAC

Nu-Cote WaterLac is a high quality 100% acrylic water-based transparent semi-gloss finish with good abrasion resistant property. It is most suitable on new parquet floors, wooden furniture, wood paneling and wooden doors. This **water-based** product features **low VOC, formaldehyde free, heavy-metals free** and **APEO free**, formulated with great care for your ease of mind when considering its effect to your health and the environment.

Colour	Clear Glossy and Coloured (See Nu-Cote Transparent Timber Series Colour Card)	
Pack Size	1 and 5 litres	
Composition	<i>Binder</i>	Pure acrylic emulsion
	<i>Pigment</i>	Pigment preparations
	<i>Solvent</i>	Water
Volume Solid	Average 40 ± 2%, varying with colours	
Recommended Dry Film thickness	30 – 50 microns (per coat)	
Drying Times *	<i>Touch Dry</i>	Within 1 hour
	<i>Hard Dry</i>	Within 2 hours
Full Cure *	3 – 4 weeks; Time for the coating to reach its full chemical/mechanical properties and will resist and perform as per the properties featured	
Over-coating Interval *	Minimum 3 hours	
Spreading Rate *	8 – 13 m ² /litre/coat (varies with roughness and porosity of substrate)	
Application	<i>Brush/Roller</i>	Use as is, thin not exceeding 5% by volume with water if necessary
	<i>Conventional Spray</i>	Thin with water to 20% by volume
	<i>Airless Spray</i>	Thin with water to 10% by volume
Surface Preparation	<i>New Unpainted Surface</i>	<i>Previous Painted Surface</i>
<i>Wood/Timber</i>	<ul style="list-style-type: none"> Ensure surface free from oil, grease and other contaminant Sand surface with abrasive paper for better adhesion and appearance 	<ul style="list-style-type: none"> Remove loose adhering paint Ensure surface is clean and dry
Recommended No. of Coat	2 to 3 coats	

* Based on recommended thickness; will vary considerably with surface characteristics, application techniques, weather and wastage.

The corresponding Safety Data Sheet (SDS) for this product shall be provided upon request.

Further inquiry and SDS request can be made to transpaint@yungkong.com

Manufactured by: **Trans Paint Coatings Sdn Bhd**. Lot 1393, Jalan Meranti, Bintawa Industrial Estate, 93450 Kuching, Sarawak, Malaysia.

Tel: +6082 334 222 Fax: +6082 339 189 Website: www.transpaint.yungkong.com

While every care has been taken to ensure the accuracy of the information contained in this data sheet, it is provided in good faith and that no liability can be accepted arising from its use. Where the conditions of use warrant it, it is recommended that the data are checked to ensure their suitability for the use envisaged.

Revision: **6 NOV 2023**

<end of document>