

ECLITE EMULSION

This is a cost-effective emulsion paint specially formulated for interior walls. It gives a very comfortable and non-reflective appearance and has strong resistance against algae and fungus. This **water-based** product features **low VOC** and **heavy-metals free**, formulated with great care for your ease of mind when considering its effect to your health and the environment.

Colour	White	
Pack Size	7 and 18 litres	
Composition	<i>Binder</i>	Vinyl acetate/acrylic ester copolymer emulsion
	<i>Pigment</i>	Inorganic, organic pigments and mineral extenders
	<i>Solvent</i>	Water
Volume Solid	36 ± 2%	
Recommended Dry Film thickness	30 – 50 microns (per coat)	
Drying Times *	<i>Touch dry</i>	Within 30 minutes
	<i>Hard Dry</i>	Within 1 hour
Full Cure *	3 – 4 weeks; Time for the coating to reach its full chemical/mechanical properties and will resist and perform as per the properties featured	
Over-coating Interval *	2 hours minimum	
Spreading Rate *	7 – 11 m ² /litre/coat	
Application	<i>Brush/Roller</i>	Use as is, thin not exceeding 5% by volume with water if necessary
	<i>Conventional Spray</i>	Thin with water to 20% by volume
	<i>Airless Spray</i>	Thin with water to 10% by volume
Surface Preparation	<u><i>New Unpainted Surface</i></u>	<u><i>Previous Painted Surface</i></u>
<i>Concrete/Masonry</i>	<ul style="list-style-type: none"> Ensure surface is clean and dry Apply appropriate sealer 	<ul style="list-style-type: none"> Remove loose paint film by hard scraping/high pressure water jet Treat fungi, algae or mould with fungicidal wash Ensure dry off before painting
Recommended Painting System	<u><i>Sequence</i></u>	<u><i>Product</i></u>
<i>Concrete/Masonry</i>	Primer/Undercoat (1 coat) Finish (2 coats)	ECLITE SEALER/ECLITE UNDERCOAT ECLITE EMULSION

* Based on recommended thickness; will vary considerably with surface characteristics, application techniques, weather and wastage.

The corresponding Safety Data Sheet (SDS) for this product shall be provided upon request.

Further inquiry and SDS request can be made to transpaint@yungkong.com

Manufactured by: **Trans Paint Coatings Sdn Bhd**. Lot 1393, Jalan Meranti, Bintawa Industrial Estate, 93450 Kuching, Sarawak, Malaysia.

Tel: +6082 334 222 Fax: +6082 339 189 Website: www.transpaint.yungkong.com

While every care has been taken to ensure the accuracy of the information contained in this data sheet, it is provided in good faith and that no liability can be accepted arising from its use. Where the conditions of use warrant it, it is recommended that the data are checked to ensure their suitability for the use envisaged.

Revision: **6 NOV 2023**

<end of document>